

TBA



PUMPING SOLUTIONS FOR WHERE IT REALLY MATTERS



SPP PUMPS IS A LEADING MANUFACTURER OF CENTRIFUGAL PUMPS AND SYSTEMS.

For more than 130 years, the company's robust, trusted engineering has provided critical performance across diverse industry applications including oil and gas, water, power generation, construction, mining and fire protection.

PROVEN QUALITY

Our customers' pumping applications are invariably demanding – typically operating in hostile, arduous or extreme temperature environments, where quality matters. Using the most advanced computer testing in the world, we design, simulate, evaluate, refine and manufacture all products and packaged systems here in the UK.

DEDICATED EXPERTISE

Our engineering team, commonly regarded as the best in the industry, has real-world application experience across multiple industry sectors. Our ability and knowledge to respond rapidly to demanding customer needs, is fuelled by dedicated R&D investment from the parent company Kirloskar Brothers Limited, India's largest provider of hydraulic machines and systems.

Proven quality. Dedicated expertise. World-class performance. For where it really matters, insist on SPP Pumps.

SPP PUMP APPLICATION MATRIX

Pump Category	SPP Model	Fire	Chemical	Pulp and Paper	Mining and Minerals	Power Generation	Oil Refining and Gas Processing	Steel Metals	Water Industry	Wastewater Industry	Food and Beverage	Transformer Oil Cooling	Nature of Liquid or Medium						Pumps as Turbine	Refer to Page
													High Pressure	Corrosive	High Temperature (580°F, 268° and greater)	Fertilizer	Solids Handling	Solids		
End Suction	Unistream	●				●		●	●	●	●							●	11	
	Eurostream	●				●		●	●	●	●								11	
	Instream	●				●		●	●	●	●								11	
	Aquastream – Mixed Flow	●				●		●	●	●	●								12	
	KPD	●	●			●	●	●	●			●		●					12	
	GK	●				●		●	●			●							12	
Split Case	LLC	●				●	●	●	●	●								●	13	
	Hydrostream	●				●	●	●	●	●									13	
	Thrustream	●				●	●	●	●	●									13	
	UP					●		●	●	●									14	
Vertical	LLC VTP	●				●	●		●	●									14	
	Vertical Turbine	●	●			●	●	●	●	●				●	●				14	
	Borehole								●										15	
	KPD-S	●	●			●		●	●					●	●		●		15	
Multi-stage / Multi-outlet	RKB/CD	●	●		●	●		●	●				●						15	
	CF		●			●			●				●						16	
Solids Handling and Solids	SHM		●	●					●	●							●	●	16	
	SHL		●	●					●	●							●	●	16	
	SHS		●	●					●	●							●	●	17	
	Freeway								●	●							●	●	17	
	Freestream									●							●	●	17	
	Solids Diverter								●	●							●		18	
Fire Packages	Package Sets	●																	18	
	Prepackaged Pump Houses	●																	18	
API	OH2 – KESS		●			●	●							●	●	●			19	
	BB1 – Hydrostream					●	●												19	
	BB2 – KBSD		●			●	●							●	●	●			19	
	BB2 – KBTS/D		●			●	●							●	●	●			20	
	BB3 – KB3S/D		●			●	●						●	●	●	●			20	
	BB4 – KBSH/KBDH		●			●	●						●	●	●	●			20	
	BB5 – KBDS/KBDD		●			●	●						●	●	●	●			21	
	VS1 & VS6 – KVSL/KVSH		●			●	●							●	●	●			21	
Contractors Pumps	Q-Series			●	●				●	●							●	●	21	
	Medium Head Open Set (Diesel)			●	●				●	●							●	●	22	
	Highflow			●	●				●	●							●	●	22	
	Medium Head Open Set (Electric)			●	●				●	●							●	●	22	
	Hydraulic Submersibles			●	●				●	●							●	●	23	
Transformer Oil	AT Inline Range											●							23	
	AT Elbow Range											●							23	

END SUCTION



UNISTREAM

WATER	FIRE	STANDARD
INDUSTRY		

CONFIGURATION

Horizontal electric motor or engine driven

DISCHARGE & PERFORMANCE

- 32 mm to 150 mm
- Outputs up to 504 m³/h
- Heads up to 105 m

FEATURES

- Horizontal DIN 24255 Electric Motor
- 41 models
- Wide choice of materials
- Centreline discharge
- Back pull-out rotating element can be removed without disturbing pipe work
- Impellers cut to duty
- High interchangeability – just three shaft modules cover the entire range
- Suitable for baseplate mounting with coupling
- Approved to LPCB, FM and/or UL Standards
- In compliance with NFPA 20
- Used in pump as turbine applications



EUROSTREAM

WATER	FIRE	STANDARD

CONFIGURATION

Horizontal close coupled electric motor driven

DISCHARGE & PERFORMANCE

- 32 mm to 100 mm
- Outputs up to 360 m³/h
- Heads up to 105 m

FEATURES

- Close coupled pump set. Choice of 190 motor/pump combinations
- Space saving
- Most cost effective solution
- Incorporates mechanical seal to DIN 24960
- Impellers cut to duty
- High interchangeability
- TEFC IE2 motors fitted as standard
Other motor options available
- Unique SPP Pumps design taper locking system simplifies fitting stub shafts to standard motors
- Uses standard metric TEFV or Drip Proof motors
- Stub shafts fit directly onto standard motor shaft – no drilling or priming required
- Back pull-out
- Rotating element can be removed without disturbing pipe work



INSTREAM

WATER	FIRE	STANDARD
INDUSTRY		

CONFIGURATION

Vertical close coupled electric motor driven

DISCHARGE & PERFORMANCE

- 40 mm to 100 mm
- Outputs up to 216 m³/h
- Heads up to 65 m

FEATURES

- Close coupled in-line design
- Simple installation and easy service back pull-out design
- Cost-effective solution
- TEFC IE2 motors fitted as standard
- High interchangeability – rotating element will interchange with Eurostream
- Mechanical seal as standard
- Impellers cut to duty

END SUCTION



AQUASTREAM – MIXED FLOW

WATER FIRE STANDARD
INDUSTRY

CONFIGURATION

Horizontal or vertical electric motor or engine driven

DISCHARGE & PERFORMANCE

- 200 mm to 650 mm
- Outputs up to 6480 m³/h
- Heads up to 28 m

FEATURES

- High efficiency pump range
- Mixed flow impeller will handle clean or dirty water containing small solids
- Heavy duty oil lubricating bearing bracket
- Soft packed
- An excellent range of pump sizes available
- Suitable for baseplate mounting with coupling



KPD

WATER FIRE INDUSTRY

CONFIGURATION

Horizontal or vertical electric or engine driven process pump

DISCHARGE & PERFORMANCE

- Delivery up to 200 mm
- Outputs up to 900 m³/h
- Heads up to 225 m

FEATURES

- Back pull-out arrangement
- Bearing oil cooling arrangement
- Steam jacket arrangement
- Centre line mounting
- Mechanical seal or gland packed
- Temperatures range -50 to 350 °C



GK

WATER FIRE INDUSTRY

CONFIGURATION

Horizontal, electric motor

DISCHARGE & PERFORMANCE

- Delivery up to 100 mm
- Outputs up to 800 m³/h
- Heads up to 140 m

FEATURES

- Back pull-out
- ISO 5199 / 2858 / EN:22858
- Enclosed impeller only
- Gland packed
- Balanced impeller
- Top centre line discharge
- No venting required

SPLIT CASE



LLC

WATER	FIRE	INDUSTRY
OIL & GAS		

CONFIGURATION

Horizontal, vertical open shaft, vertical direct mounted electric motor or horizontal engine driven

DISCHARGE & PERFORMANCE

- 125 mm to 600 mm
- Outputs to 9000 m³/h
- Heads up to 300 m

FEATURES

- Axially split casing – rotating element can be removed without disturbing pipework
- Exceptional hydraulic efficiencies
- Double and single entry back to back impellers reduce end thrust, increase efficiency and bearing life
- Modular design for maximum interchangeability. Multiple impeller selections
- Stainless steel impellers and shaft as standard
- Internal high efficiency coating as standard
- Cartridge mechanical seals as standard
- Double row thrust bearing
- Wide operating range and extended bearing life
- Reduced efficiency degradation
- Approved to FM and/or UL standards
- In compliance with NFPA 20
- Used in pump as turbine applications



HYDROSTREAM

WATER	FIRE	INDUSTRY
OIL & GAS		

CONFIGURATION

Horizontal, vertical open shaft, vertical direct mounted electric motor or horizontal engine driven

DISCHARGE & PERFORMANCE

- 25 mm to 600 mm
- Outputs to 9000 m³/h
- Heads up to 275 m

FEATURES

- Axially split casing – rotating element can be removed without disturbing pipework
- High hydraulic efficiencies
- Double and single entry back to back impellers reduce end thrust, increase efficiency and bearing life. Shaft sleeves are standard
- 62 models. Module design for maximum interchangeability. Multiple impeller selections
- Wide choice of materials
- Grease or oil lubrication
- Soft packing or mechanical seals
- API options available for off site applications
- Approved to FM and/or UL standards
- In compliance with NFPA 20



THRUSTREAM

WATER	FIRE	STANDARD
INDUSTRY	OIL & GAS	

CONFIGURATION

Horizontal, vertical open shaft, vertical direct mounted electric motor or horizontal electric motor or engine driven

DISCHARGE & PERFORMANCE

- 65 mm to 350 mm
- Outputs up to 3500 m³/h
- Heads up to 300 m

FEATURES

- Axially split casing – rotating element can be removed without disturbing pipework
- High hydraulic efficiencies
- Double entry impellers reduce end thrust, increase efficiency and bearing life
- Shaft sleeves fitted as standard for soft packed pumps and as an alternative for mechanical seals. Stainless steel shafts fitted as standard for mechanical seals
- 40 models. Module design for maximum interchangeability
- Grease lubrication
- Soft packing or mechanical seals
- Suitable for baseplate mounting with coupling
- Approved to LPCB, FM and/or UL standards
- In compliance with NFPA 20

SPLIT CASE



UP

WATER INDUSTRY

CONFIGURATION

Horizontally axially split casing, single stage, double or single suction, single or double volute with horizontal shaft

DISCHARGE & PERFORMANCE

- Delivery up to 1200 mm
- Outputs up to 24,120 m³/h
- Head up to 180 m

FEATURES

- Rotating assembly accessible for inspection or maintenance by removing upper half casing without disturbing suction and delivery piping and motor
- Horizontal execution (standard) or vertical execution (optional)
- Vertical pump, direct drive or with universal shaft arrangement
- High hydraulic and overall efficiency due to superior design and manufacturing techniques
- Good suction performance and low NPSH
- Stable characteristics, minimum maintenance required, vibration free performance
- High reliability
- Mechanical seal or gland packed
- 50 or 60 hz operation

VERTICAL



LLC VTP

WATER INDUSTRY OIL & GAS

CONFIGURATION

Vertical lineshaft, vertical electric motor or engine driven, dry or wet well

DISCHARGE & PERFORMANCE

- 200 mm to 600 mm
- Outputs up to 3960 m³/h
- Heads up to 170 m
- Pumping length up to 60 m

FEATURES

- Cartridge mechanical seal
- Spacer couplings minimise seal change downtime
- High grade materials – stainless steel impellers & shafts
- Muff couplings aid assembly / disassembly
- Flanged riser pipework
- Modular design
- Extended thrust bearing life
- Stiff shaft construction
- Dry and wet well installations



VERTICAL TURBINE. AXIAL FLOW/MIXED FLOW & PROPELLER

WATER FIRE INDUSTRY
OIL & GAS

CONFIGURATION

Vertical lineshaft, vertical electro submersible, vertical electric motor or engine driven, dry or wet well

DISCHARGE & PERFORMANCE

- 100 mm to 2200 mm
- Outputs up to 40,000 m³/h
- Heads up to 200 m

FEATURES

- Space saving
- Low maintenance costs
- High hydraulic efficiency
- Priming problems eliminated. Pump end submerged in liquid
- 60 models, with bowls, heads and columns optimised for performance and cost
- Wide choice of materials
- Diffuser bowls ensure balanced axial loading
- Soft packing or mechanical seals
- API construction
- Approved to FM and UL standards, all of which are compliant to NFPA 20
- Nuclear certification
- Dry and wet well installations



BOREHOLE

INDUSTRY

CONFIGURATION

Vertical borehole pump, electric motor

DISCHARGE & PERFORMANCE

- Borewell size 150 mm
- Outputs 44 m³/h
- Head 1 m to 447 m

FEATURES

- Higher head per stage resulting in achieving same head with less number of stages
- Better surface finish hence better efficiency and consistent performance
- Lesser weight and lesser height resulting in ease of installation and transportation
- CED coating cast iron components long life & rust free
- Loading of pipes improves
- For longer life Teflon Carbon Thrust bearing



KPD-S

FIRE INDUSTRY

CONFIGURATION

Vertical sump pump

DISCHARGE & PERFORMANCE

- Delivery size from 20 mm to 150 mm
- Outputs 0.5 to 560 m³/h
- Head 2.3 m to 150 m

FEATURES

- Pit depth up to 5.5 m
- Temp range from -10 to 150 °C
- Self priming
- Available in various materials
- Mechanical seal or gland packed



MULTISTREAM CD / RKB

WATER FIRE INDUSTRY

CONFIGURATION

Consists of a number of ring section diffuser casings bolted suction and delivery casing

DISCHARGE & PERFORMANCE

- CD Delivery 100 mm to 125 mm
- CD Outputs up to 500 m³/h
- CD Heads up to 60 bar (Fire applications)
- RKB Delivery 32 mm to 250 mm
- RKB Outputs up to 850 m³/h
- RKB Heads up to 850 m

FEATURES

- CD for fire applications
- RKB for industrial applications
- Mechanical seal or gland packed
- Suction flange oriented left or right
- Vertical mounting
- Low NPSH
- Available as a canned or vertical turbine type arrangements
- Approved to LPCB, FM and/or UL standards, all of which are compliant to NFPA 20



CF

INDUSTRY

CONFIGURATION

Multi-stage pump with modular construction

DISCHARGE & PERFORMANCE

- Delivery size up to 50 mm
- Outputs up to 20 m³/h
- Head up to 315 m
- Temp up to 120 °C

FEATURES

- Channel multi-stage, Modular Construction
- Gland Packed / Mechanical Seal
- Electrical Drive / Engine Drive
- Self priming
- Conforming to DIN 24254



SHM

WATER **INDUSTRY**

CONFIGURATION

Horizontal non-clog pumps having single stage, single suction with back pull out type design

DISCHARGE & PERFORMANCE

- Delivery up to 200 mm
- Outputs up to 800 m³/h
- Head up to 90 m

FEATURES

- Back pull-out design
- Solids handling up to 105 mm
- Impeller type non clog
- Oil or grease lubricated bearing housing
- Mechanical seal or gland packed
- Temp up to 140 °C



SHL

WATER **INDUSTRY**

CONFIGURATION

Horizontal and vertical single stage solids handling pump

DISCHARGE & PERFORMANCE

- Delivery up to 900 mm
- Outputs 13,000 m³/h
- Heads up to 82 m

FEATURES

- Solids handling up to 300 mm
- Mechanical seal or gland packed
- Impeller enclosed or semi open type
- Grease or oil lubrication
- Available in various materials



SHS

INDUSTRY

CONFIGURATION

Vertical non-clog pumps for wet pit applications, these pumps can be offered with a column length up to 6.5 m

DISCHARGE & PERFORMANCE

- Delivery up to 300 mm
- Outputs up to 800 m³/h
- Head up to 90 m

FEATURES

- Solids handling up to 105 mm
- Mechanical seal or gland packed
- Available in various materials
- Impeller non clog type
- The pump unit is suspended by a column pipe which also protects the transmission shaft.



FREWAY

WATER

INDUSTRY

CONFIGURATION

Vertical direct mounted or open shaft electric motor driven

DISCHARGE & PERFORMANCE

- 75 mm to 600 mm
- Outputs up to 4320 m³/h
- Heads up to 100 m

FEATURES

- Separate pump and motor
- Pump rotating element incorporation bearing and seal arrangement
- Hydraulic loads taken by pump bearing assembly, not motor bearings
- Double cartridge mechanical seal option
- Hydraulic design – low specific speed designs
- Bespoke wear liner
- Large solids passing capacity
- Hardened metallic impeller option
- Positively locked impeller



FREESTREAM

WATER

INDUSTRY

CONFIGURATION

Horizontal, vertical open shaft, vertical direct mounted

DISCHARGE & PERFORMANCE

- Delivery up to 200 mm
- Outputs up to 1080 m³/h
- Heads up to 90 m

FEATURES

- High efficiency spiral vane impeller designed to handle large solids, thick sludges and fibrous materials
- Impeller cut to specific duty
- Modular construction to maximise interchangeability
- Steep H/Q curves mean that changes in pumping head can be tolerated without significant loss of efficiency
- Soft packing or mechanical seals



SOLIDS DIVERTER

WATER INDUSTRY

CONFIGURATION

Electric motor drive, tank packages

DISCHARGE & PERFORMANCE

- 100 mm to 200 mm
- Outputs up to 75 m³/h
- Heads up to 40 m

FEATURES

- Automatic totally enclosed sewage pumping station
- Low noise levels
- High efficiency pumping units
- Minimum maintenance – unique system avoids solids passing through pumps so eliminates blockage
- 4 sizes of plant available to suit inflow conditions
- Suitable for basement installation
- Clean and environmentally friendly
- Economical to operate



PACKAGE SETS

FIRE OIL & GAS

CONFIGURATION

Single or multiple pump package sets, horizontal end suction close and long coupled, split case long coupled, multi-stage multi-outlet and vertical turbine all electric motor or engine driven

DISCHARGE & PERFORMANCE

- End Suction (Single Stage) – 32 mm to 150 mm. Outputs up to 500 m³/h Heads up to 15.2 bar
- Outputs up to 230 l/s Heads up to 60 bar
- Split Case – 80 mm to 300 mm. Heads up to 44.5 bar (Approved fire set)
- Multi-stage multi-outlet – 100 mm to 125 mm. Outputs up to 315 l/s. Heads up to 60 bar
- Vertical Turbine – 200 mm to 508 mm Outputs up to 9000 m³/h
- Multi-stage / multi-outlet – 50 mm to 250 mm. Outputs up to 850 m³/h. Heads up to 850 m. Up to 140 °C

FEATURES

- Meeting the requirements of worldwide insurance and approvals bodies
- End Suction – Centreline discharge back pull-out rotating element can be removed without disturbing pipe work
- End Suction – Close coupled, space and cost saving solution
- Axially split case rotating element can be removed without disturbing pipework
- Rigid, box-section baseplates for end suction and split case long coupled packages
- Stainless steel shaft with tight tolerances designed to transmit the maximum load across full pump curve
- Bearing arrangements of ample proportion
- IE2 motors fitted as standard
- Impellers machined and hand finished to meet customer duty



PREPACKAGED PUMP HOUSES

FIRE OIL & GAS

CONFIGURATION

Design and supply of enclosure and installation inside of main fire pump sets, jockey pump, controllers, starters, all internal pipe work, test line, flow meter, wiring and lighting to provide a fully packaged unit.

DISCHARGE & PERFORMANCE

- End Suction (Single Stage) – 32 mm to 150 mm
- Outputs up to 500 m³/h. Heads up to 15.2 bar
- End Suction (multi-stage) – 100 mm to 125 mm
- Outputs up to 830 m³/h. Heads up to 60 bar
- Split Case – 80 mm to 300 mm
- Outputs up to 9000 m³/h. Heads up to 44.5 bar
- Vertical Turbine – 200 mm to 508 mm
- Outputs up to 315 l/s. Heads up to 31.1 bar

FEATURES

- Delivered complete, ready for immediate installation on simple foundations
- Ease of site installation and connection
- Single responsibility for complete pump house
- Fully tested and pre-commissioned using advanced computerised testing facilities
- Individually engineered to customer requirements
- Containerised CAD design
- Wall insulation reduces environmental noise



OH2 – KESS

OIL & GAS INDUSTRY

CONFIGURATION

Single stage, single suction, overhung, radially split, centreline mounted

DISCHARGE & PERFORMANCE

- Outputs up to 2000 m³/h (8800 US.gpm)
- Head up to 400 m (1300 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- Back pull-out casing to aid maintenance
- Parts interchangeability between models
- Low NPSH performance (inducer available for extreme conditions)
- Reduced maintenance due to balanced axial thrust from impeller wear-ring and balance holes
- Bearing lubrication by oil flinger as standard. Oil mist retrofit option available



BB1 – HYDROSTREAM

OIL & GAS INDUSTRY

CONFIGURATION

Single stage, between bearing, axially split, foot mounted

DISCHARGE & PERFORMANCE

- Outputs up to 9000 m³/h (40,000 US.gpm)
- Head up to 500 m (1640 ft)

FEATURES

- Generally in compliance with API 610 standards
- Single stage double entry enclosed impeller
- High efficiency product
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from double entry impeller
- Bearing lubrication by oil flinger
- Serviceable without removing suction and discharge pipework
- Ease of access to rotating assembly by axially split casing design
- Removal of bearings and seals without splitting casing



BB2 – KBSD

OIL & GAS INDUSTRY

CONFIGURATION

Single stage, between bearing, radially split, centreline mounted

DISCHARGE & PERFORMANCE

- Outputs up to 6000 m³/h (26,420 US.gpm)
- Head up to 550 m (1800 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- Single stage double entry enclosed impeller
- High efficiency
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from double suction impeller
- Bearing lubrication by oil flinger. Oil mist retrofit option available
- Serviceable without removing suction and discharge pipework
- Easy fitment and removal of coupling with tapered pump shaft end



BB2 – KBTS/D

OIL & GAS INDUSTRY

CONFIGURATION

Two stage, between bearing, radially split, centreline mounted

DISCHARGE & PERFORMANCE

- Outputs up to 1500 m³/h (6600 US.gpm)
- Head up to 520 m (1700 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- KBTS: two stage, single entry, enclosed impeller
- KBTD: two stage, first stage double entry, enclosed impeller
- High efficiency
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from impeller configuration
- Serviceable without removing suction and discharge pipework
- Easy fitment and removal of coupling with tapered pump shaft end
- Bearing lubrication by oil flinger. Oil mist retrofit option available



BB3 – KB3S/D

OIL & GAS INDUSTRY

CONFIGURATION

Multi-stage, between bearing, axially split, centreline mounted, single casing

DISCHARGE & PERFORMANCE

- Outputs up to 1500 m³/h (6600 US.gpm)
- Head up to 1650 m (5500 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- KB3S: First stage single suction, multi-stage, enclosed impeller
- KB3D: First stage double suction, multi-stage, enclosed impeller
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from opposing impellers and balance piston arrangement
- Bearing lubrication by oil flinger. Oil mist retrofit option available
- Serviceable without removing suction and discharge pipework
- Ease of access to rotating assembly by axially split casing design
- Removal of bearings and seals without splitting casing
- Easy fitment and removal of coupling with tapered pump shaft end



BB4 - KBSH/KBDH

OIL & GAS INDUSTRY

CONFIGURATION

Multi-stage, between bearing, radially split, centreline mounted, single casing

DISCHARGE & PERFORMANCE

- Outputs up to 650 m³/h (2900 US.gpm)
- Head up to 2500 m (8200 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- KBSH: multi-stage, single entry, enclosed impellers
- KBDH: multi-stage, single entry, enclosed impeller (first stage double entry)
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from opposing impellers and balance piston arrangement
- Bearing lubrication by oil flinger. Oil mist retrofit option available
- Serviceable without removing suction and discharge pipework



BB5 – KBDS/KBDD

OIL & GAS INDUSTRY

CONFIGURATION

Multi-stage, between bearing, radially split, centreline mounted, double casing

DISCHARGE & PERFORMANCE

- Outputs up to 650 m³/h (2900 US.gpm)
- Head up to 2500 m (8200 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- KBDS: multi-stage, single entry, enclosed impellers
- KBDD: multi-stage, enclosed impeller (first stage double entry)
- Parts interchangeability between models
- Low NPSH performance
- Reduced maintenance due to balanced axial thrust from opposing impellers and balance piston arrangement
- Bearing lubrication by oil flinger. Oil mist retrofit option available
- Serviceable without removing suction and discharge pipework
- Easy fitment and removal of coupling with tapered pump shaft end



VS1 & VS6 – KVSL/KVSH

OIL & GAS INDUSTRY

CONFIGURATION

Single or multi-stage, vertically suspended, diffuser type single or canned casing

DISCHARGE & PERFORMANCE

- Outputs up to 1750 m³/h (7700 US.gpm)
- Head up to 1600 (9850 ft)

FEATURES

- Full package compliance with API 610 & API 682 standards
- Single or multi-shaft and column assembly for longer lengths
- Split and keyed inter-shaft coupling used
- Thrust bearing and seal serviceable without removing suction and discharge pipework
- Parts interchangeability between models
- Low NPSH performance (inducer available for extreme conditions)
- Reduced maintenance due to balanced axial thrust from impeller wear-ring and balance holes
- Bearings with non pressure fed lubrication
- Water jacketed thrust bearing
- Serviceable without removing suction and discharge pipework



Q-SERIES

AUTOPRIME

CONFIGURATION

Acoustic canopy on road tow or site trailer or skid type chassis

DISCHARGE & PERFORMANCE

- Discharge pressure up to 80 m
- Discharge flow m³/h max 560

FEATURES

- Minimal moving parts in priming system
- Durable 65 cfm vacuum pump
- Patented 'SmartPrime' system
- Single point lifter
- Lockable canopy totally enclosing unit
- Lockable control panel
- Impact resistant doors and louvre panel
- Excellent sound attenuation
- Latest emission compliant engines
- Clear air coalescence system
- Heavy-duty shaft and bearings
- Double mechanical seal
- Large double skin fuel tank
- High efficiency pump hydraulics
- Double spiral-vane impeller
- Compact manoeuvrable design
- Sewage, solids handling open impeller 'S' design
- Diesel options – Isuzu, Caterpillar, Perkins

CONTRACTORS PUMPS



MEDIUM HEAD OPEN SET (DIESEL)

AUTOPRIME

CONFIGURATION

Open configuration on four wheeled site type trailer

DISCHARGE & PERFORMANCE

- Discharge pressure up to 48 m
- Discharge flow m³/h max 380

FEATURES

- Low emission coalescer (PM/PE)
- Fuel savings with SmartPrime electric priming (PE)
- Leak free double mechanical seals
- Dry running capability
- Customer choice of the latest emission compliant engines
- High interchangeability of parts
- Heavy duty shaft and bearings
- High efficiency pump hydraulics
- Heavy duty and durable vacuum pump
- Reduced maintenance
- Integrated central lifter
- Excellent flow and head performance
- Excellent solids handling capability
- Quality design and parts offering durability
- Proven technology



HIGH FLOW

AUTOPRIME

CONFIGURATION

Open skid or trailer configuration or acoustic canopy on road tow or site trailer or skid type chassis

DISCHARGE & PERFORMANCE

- Discharge pressure up to 130 m
- Discharge flow m³/h max 2550

FEATURES

- Low emission coalescer (PM/PE)
- Fuel savings with SmartPrime electric priming (PE)
- Minimal moving parts in the priming system
- Leak free mechanical sealing
- Customer choice of the latest emission compliant engines
- High interchangeability of parts
- Heavy duty shaft and bearings
- High efficiency pump hydraulics
- Heavy duty and durable vacuum pump
- Reduced maintenance
- Excellent flow and head performance
- Excellent solids handling capability
- Quality design and parts offering durability
- Proven technology



MEDIUM HEAD OPEN SET (ELECTRIC)

AUTOPRIME

CONFIGURATION

Open skid or trailer electric motor driven

DISCHARGE & PERFORMANCE

- Discharge pressure up to 160 m
- Discharge flow m³/h max 2550

FEATURES

- Low emission coalescer (PM/PE)
- Energy savings with SmartPrime electric priming (PE)
- Minimal moving parts in the priming system
- Leak free mechanical sealing
- High interchangeability of parts
- Heavy duty shaft and bearings
- High efficiency pump hydraulics
- Heavy duty and durable vacuum pump
- Reduced maintenance
- Excellent flow and head performance
- Excellent solids handling capability
- Quality design and parts offering durability
- Proven technology
- Optional variable speed drive
- Power inlet socket for diesel generator drive or mobile site application
- Hazardous area and ATEX approved motors
- Fixed or variable speed.
Variable speed via frequency inverter.

TRANSFORMER OIL



HYDRAULIC SUBMERSIBLES

AUTOPRIME

CONFIGURATION

Open skid or trailer configuration or acoustic canopy on road tow or site trailer or skid type chassis

DISCHARGE & PERFORMANCE

- Discharge pressure up to 130 m
- Discharge flow m³/h max 2300

FEATURES

- Comprehensive choice of over 30 pump ends and over 25 power packs to ensure efficient matching
- Efficient, variable speed drive provides excellent fuel-savings
- Proven and reliable designs
- Sound attenuated power packs available
- Use of biodegradable oil as standard
- No electrical hazard as encountered with electric submersibles
- Pump ends can be bolted inline to become booster pumps
- Compact dimensions to allow access through manholes
- Minimal maintenance and low maintenance costs
- Easy set-up can be operational in a very short time
- Can be used in hazardous environments



AT - INLINE RANGE

TRANSFORMER OIL

CONFIGURATION

Inline, glandless oil submerged motor on common shaft with impeller

DISCHARGE & PERFORMANCE

- 50 mm to 250 mm
- Outputs up to 576 m³/h
- Heads up to 30 m

FEATURES

- Aluminium Casings - Robust lightweight design
- Proven long reliability in industry
- Hand built in England with British castings and European Motors
- Entire range 3D CAD modelled
- Every pump is performance and pressure tested on our warm oil test rig (documented results)
- Duty performance to your specific requirements
- Flexible to your needs - flange drillings, paint and material specifications to your needs
- Fully weatherproof
- Oil cooling circulation in:
 - Power distribution transformers
 - Locomotive transformers and converters



AT - ELBOW RANGE

TRANSFORMER OIL

CONFIGURATION

Elbow (end suction) glandless oil submerged motor on common shaft with impeller

DISCHARGE & PERFORMANCE

- 100 mm to 250 mm
- Outputs up to 792 m³/h
- Heads up to 25 m

FEATURES

- High grade cast iron casings and bronze impellers
- Proven long lifetime performance in industry
- Hand built in England with British castings and European Motors
- Every pump is performance and pressure tested on our warm oil test rig (documented results)
- Duty performance to your specific requirements
- Flange and paint to your specifications
- Fully weatherproof
- Oil cooling circulation in:
 - Power distribution transformers
 - Locomotive transformers and converters

FOR WHERE IT REALLY MATTERS ACROSS THE GLOBE

At our main manufacturing centre in the UK we strive to develop the best products using high quality engineering and manufacture. Engineered and developed to the most rigorous standards, our products are then tested in our purpose built facility that incorporates a 1.4 million litre reservoir. It's no surprise that our products are commonly regarded as the best in the industry.



TBA



www.tba.co.id | info@tba.co.id | tel: +6221-2212-8880



SPP Pumps reserve the right to continually develop and improve products. Information contained herein is for guidance only and subject to change. SPP Pumps Ltd accept no liability whatsoever for any damages either direct or consequential resulting from the use of such information.

* Applies to: Coleford Manufacturing Site, Northern Service Centre and Wales & West Service Centre.
SPP Pumps are proud to be working towards achieving this accreditation at all sites.

